TRELLEBORG

vulcan®

ECO

Description

The new Vulcan Eco is ideally suited for a wide range of applications in sheet-fed printing, especially in tough conditions and consumption is high.

Budget price blanket.

MAIN APPLICATION

Commercial Sheetfed

Vulcan Eco is available in 4-ply, (1,96 mm) thickness.

Standard

Vulcan Eco

The product at a glance

PRINTING SURFACE COLOUR	Blue
THICKNESS (mm)	1,96
SURFACE ROUGHNESS (Ra micron)	1,0
INK COMPATIBILITY	Conventional
ELONGATION (%)	<0,9
TENSILE STRENGHTS (N/mm)	>60
AVERAGE LOAD VALUE N/cm2 @ 0,23 mm Indentation	250
WATER SOLVENT PROTECTED	No
ADDITIONAL INFORMATION	
PRINT QUALITY	Vulcan print quality on a variety of stocks

IF YOU WOULD LIKE TO SPEAK TO SOMEONE ABOUT THIS PRODUCT OR ANY OTHER VULCAN PRODUCT PLEASE SPEAK TO ONE OF OUR DEDICATED TEAM: printing@trelleborg.com

The information contained in this document is intended to provide guidance. The information is NOT a specification and all figures in the document are nominal.
This document and the information it contains do not create any warranties for any product and Trelleborg Printing Solutions. disclaims any warranty of merchantability or fitness for a particular purpose for the product described in this document. This document discloses information that is proprietary to Trelleborg Printing Solutions. The receipt or possession of the document does not confer any right to reproduce or disclose the document, any information contained in it, or any physical article or device, or to practice any method or process except by written agreement with Trelleborg Printing Solutions. Trelleborg Printing Solutions is committed to the ongoing development of its products. For that reason, Trelleborg Printing Solutions reserves the right to alter the actual specifications of its products without prior notice.